

aSa Tracking Solution Comparison



TouchTracker with Tablet PC



TouchTracker with Panel PC

Overview	Industrial-grade PC with color touch-screen interface. Self-contained unit.	Industrial-grade PC with color touch-screen interface. Panel PC mounted inside gasketed metal box.
Screen Size	10.4"	8.4"
Screen Resolution	1024 x 768	800 x 600
Temperature Range	-20° to 60° C	0° to 50° C
Dust and Water Resistance	Entire unit rated extremely high for dust and water protection.	Front of unit rated extremely high for dust and water protection; back is protected by gasketed box.
Hard Drive	Industrial SSD hard drive. No moving parts: extremely resistant to shock, vibration, and extreme temperatures.	Standard PC hard drive. Although protected by the metal box, spinning drive is more vulnerable to shock, vibration, and extreme temperatures.
Wireless Connectivity	Built-in Wi-Fi	Add-on cost for wireless card and antenna
Ports	2 USB ports, 1 RJ-45 Ethernet port, 1 RS-232 COM port	2 USB ports, 1 RJ-45 Ethernet port, 1 RS-232 COM port
Warranty	1 year standard warranty. Optional 3-year no-fault warranty protects against accidental damage.	1 year standard warranty.
Mounting Options	Adjustable arm allows you to easily position and tilt the console based on operator needs.	Floor-mounted pedestal, or mount the console box to the surface of your equipment.

